


Multi Construction Chemicals (PTY)LTD

Tel: (011) 864 4654/5 | Fax: (011) 864 4406 / 908 5336

Email : mcc@mccsa.co.za

www.mccsa.co.za



Reg. No : 1986/002014/07

9 Vereeniging Road, Alrode 1449
PO Box 124138, Alrode 1451, South Africa
Reg. No : 1986/002014/07

MULTI PACK 2500 SERIES

Non Seismic Grout Ready-to-Use, Non-Shrink, Fluid High Yield Grout

Description

MULTI PACK 2500 a specially formulated high yield grout providing permanent active support on previously installed timber / grout / reinforced concrete packs

Advantages

MULTI PACK 2500 provides:

- * A pre-mixed grout that hardens free of bleeding and settlement
- * A grout that does not rely on gas generating chemicals to provide the non-shrink properties
- * A high yield grout mixed in the ration of 1 part MULTI PACK 2500 to 2.5 parts of potable water by mass
- * A grout that hardens within 1 hour and can then withstand a blast after that same period
- * A grout that will help prevent blast out of the pre-stressed pack
- * An in situ grout that will follow the contours of the hanging as well as the upper end of the pack
- * A grout that is easily mixed and quickly installed
- * A grout that eliminates the tedious and lengthy operation of blocking and wedging

Typical Properties

Compressice Strengths

2 hours	0.5 MPA
1 Day	2.5 MPA
7 Days	4.0 MPA

Pot Life

The grout has a minimum pot life of 20 minutes and starts forming a solid gel after 45 minutes.

Directions for Use

Measure the required quantity of water into a mixer slowly adding MULTI PACK 2500 while agitating. Mix for approximately 2 minutes then pump the blended product into the ore-positioned grout bags.

Packaging

Supplied in 11,0kg woven polypropylene moisture resistant bags

Quality Assurance

MULTI CONSTRUCTION CHEMICALS (PTY) LTD's production and testing programmes comply with all local and international testing standards.