


# Multi Construction Chemicals (PTY)LTD

Tel: (011) 864 4654/5 | Fax: (011) 864 4406 / 908 5336

Email : [mcc@mccsa.co.za](mailto:mcc@mccsa.co.za)

[www.mccsa.co.za](http://www.mccsa.co.za)



Reg. No : 1986/002014/07

9 Vereeniging Road, Alrode 1449  
PO Box 124138, Alrode 1451, South Africa  
Reg. No : 1986/002014/07

## MULTI PACK 2500 SERIES

Non Seismic Grout Ready-to-Use, Non-Shrink, Fluid High Yield Grout

### Description

MULTI PACK 2500 a specially formulated high yield grout providing permanent active support on previously installed timber / grout / reinforced concrete packs

### Advantages

MULTI PACK 2500 provides:

- \* A pre-mixed grout that hardens free of bleeding and settlement
- \* A grout that does not rely on gas generating chemicals to provide the non-shrink properties
- \* A high yield grout mixed in the ration of 1 part MULTI PACK 2500 to 2.5 parts of potable water by mass
- \* A grout that hardens within 1 hour and can then withstand a blast after that same period
- \* A grout that will help prevent blast out of the pre-stressed pack
- \* An in situ grout that will follow the contours of the hanging as well as the upper end of the pack
- \* A grout that is easily mixed and quickly installed
- \* A grout that eliminates the tedious and lengthy operation of blocking and wedging

### Typical Properties

#### Compressice Strengths

2 hours	0.5 MPA
1 Day	2.5 MPA
7 Days	4.0 MPA

### Pot Life

The grout has a minimum pot life of 20 minutes and starts forming a solid gel after 45 minutes.

### Directions for Use

Measure the required quantity of water into a mixer slowly adding MULTI PACK 2500 while agitating. Mix for approximately 2 minutes then pump the blended product into the ore-positioned grout bags.

### Packaging

Supplied in 11,0kg woven polypropylene moisture resistant bags

### Quality Assurance

MULTI CONSTRUCTION CHEMICALS (PTY) LTD's production and testing programmes comply with all local and international testing standards.