Masonry Cement Composites (Pty) Ltd

Registration Number: 2014/263264/07
VAT No: 4090268972
27 Reuben Kaye Road, Parow Industrial, 7493
Tel: 021-934 0374 / Whatsapp: 068 006 4419

Generated on: 2026-11-11 20:10:50

Colour Retainer



SKU: MWMCR

TECHNICAL DATASHEET

COLOUR RETAINER
Colour Retainer for Pigmented Cementitious Screeds

COLOUR RETAINER is a milky white liquid applied to pigmented cementitious screeds before final application of the clear topcoat. This prevents over darkening of the screed colour by the topcoat and acts as a bond between the dense screed surface and the topcoat.

TYPICAL APPLICATION
When applied by brush or spray to surfaces of face brickwork, natural stonework, concrete, paint and asbestos sheeting, it penetrates deeply beneath the surface to line the pores with a thin acrylic coating.

ADVANTAGES
• Deep penetrating into substrates

• Enhances bond to the topcoat
• Economical
• Easy to apply
• Hardens the screed surface
• Excellent adhesion

WATCH POINTS

• Take up excess product on the floor – do not allow to pool
• Only apply over the topcoat once the colour retainer has dried to sight and touch
• Ensure screed surfaces are dust free before application

DIRECTIONS FOR USE
Surface Preparation:
The surface to be treated should be dry and free of dust.

Priming:
Dilute the COLOUR RETAINER with water at a 1:1 ratio. Apply directly to screed surfaces using a PVA roller or spray application and allow to draw in. If the substrate is very porous, another application may be required. Ensure all areas are thoroughly wet with the primer and take up any product that pools on the surface and does not draw into the substrate. Allow to dry out.

Application:
Once the COLOUR RETAINER has dried out to sight and touch, the surface is ready to be sealed with the topcoat sealer.

TYPICAL PROPERTIES

Density 1.0g/cm3
Mixing Ratio 1:1 with water
Appearance White liquid
Drying Time 4-8 hours
Application Temp. 5 - 35°C
Colour on Drying Clear
Coverage 8m2/litre on dilution

Equipment Care
Clean all equipment immediately after use with water.

Warranty
Masonry Cement Composites (PTY) Ltd products have a manufacturing defect free warranty. Products, when applied as stipulated in this technical datasheet, will perform as specified without manufacturing defect.
REVISION: 5.2