


# Multi Construction Chemicals (PTY)LTD

Tel: (011) 864 4654/5 | Fax: (011) 864 4406 / 908 5336

Email : [mcc@mccsa.co.za](mailto:mcc@mccsa.co.za)

[www.mccsa.co.za](http://www.mccsa.co.za)



Reg. No : 1986/002014/07

9 Vereeniging Road, Alrode 1449  
PO Box 124138, Alrode 1451, South Africa  
Reg. No : 1986/002014/07

## MULTIPRIME 1100 Silane Primer

### Description

MULTIPRIME 1100 a single pack primer specifically formulated to be used in conjunction with both MULTISEAL Polyurethane and Polysulphide joint sealants.

### Typical Applications

An adhesion promoter between our MULTISEAL Polyurethane and Polysulphide sealants and a large variety of inorganic substrates such as masonry, steel, glass and ceramics.

### Advantages

Ease of application and high spreading rate combine to make this product an economical primer system. Application of sealant may be made immediately after applying the primer.

### Composition

A specific blend of organo functional silanes

### Typical Properties

Specic Gravity:	0.6
Spreading rate:	10 - 15m <sup>2</sup> / litre
Application Temperature:	5°C to 40°C
Storage life:	6 months

### Directions for Use

Use Brush apply to both non-absorbent and non-friable surfaces and apply the sealant within 3 hours.

### Watchpoints

Flammable - use only in well-ventilated areas and away from naked flames, if surfaces are friable, use MULTIPRIME 1308 as the recommended primer.

### Packaging

Supplied in 250 ml, 500 ml, 1 litre and 5 litre bottles

### Quality Assurance

MULTI CONSTRUCTION CHEMICALS (PTY) LTD's production and testing programmes comply with local testing standards.