


# Multi Construction Chemicals (PTY)LTD

Tel: (011) 864 4654/5 | Fax: (011) 864 4406 / 908 5336

Email : [mcc@mccsa.co.za](mailto:mcc@mccsa.co.za)

[www.mccsa.co.za](http://www.mccsa.co.za)



Reg. No : 1986/002014/07

9 Vereeniging Road, Alrode 1449  
PO Box 124138, Alrode 1451, South Africa  
Reg. No : 1986/002014/07

## MULTI TILE BOND 555 Adhesive and Grout Additive

### Description

MULTI TILE BOND 555 is a milky white liquid, produced from styrene and butadiene by high-pressured emulsion polymerisation. The latex contains microscopic particles of synthetic rubber, dispersed in an aqueous solution.

### Typical Applications

MULTI TILE BOND 555 replaces the mixing water when using cement based MULTI TILE ADHESIVES and MULTI TILE GROUTS in the following facilities:

- Abattoirs, breweries and food processing areas
- Swimming pools and continuously wet areas
- Tiling onto smooth trowelled floors and walls
- In areas where regular temperature changes occur

It is also added to the mixing water at a ratio of 1:1 when encountering difficult applications:

- In difficult and complicated conditions
- In permanently wet conditions
- To increase water resistance
- To increase bond and flexural strength

### Directions for Use

#### Surface Preparation

Follow preparation instructions pertaining to the adhesive or grout being used.

#### Dosage Rate

Use as directed for the specific adhesive and grout products

#### Watchpoints

- \* Cement based products will dry a shade darker and setting times will be extended  $\pm$  12 hours with the addition of MULTI TILE BOND 555.
- \* Clean face of tiles before adhesive / grout hardens
- \* Do not ingest and keep away from children and pets.
- \* Do not empty into drains

#### Packaging

Supplied in 1 litre and 5 litre bottles and in 25 litre drums

#### Quality Assurance

MULTI CONSTRUCTION CHEMICALS (PTY) LTD's production and testing programmes comply with all local and international testing standards.